

CFM/CMM Thermo-Anemometer

**Model: DT-850**



**Features:**

Display Air Flow (CFM/CMM), or Air Velocity plus Temperature & Max/Min/Avg value
Easy to set Area dimensions (cm <sup>2</sup> ) stored in the meter's internal memory for the next power on
Resolution of 0.01m/sec
20 points average for Air Flow
Super large LCD Backlit Display
3% velocity accuracy via low friction 2.83"D (72mm) ball bearing vane wheel on 3.9ft (120cm) cable
Low battery indication and Auto Power Off

**Specifications:**

Air Velocity	Range	Accuracy
m/s (meter per second)	0.40~30.00	±3% ±0.20m/s
ft/min (feet per minute)	80~5900	±3% ±40ft/min
km/h (kilometers per hour)	1.4~108.0	±3% ±0.8km/h
MPH (miles per hour)	0.9~67.0	±3% ±0.4MPH
Knots (nautical miles per hour)	0.8~58.0	±3% ±0.4knots
Air Temperature	-10 to 60°C (14 to 140°F)	± 2.0°C (±4.0°F)
Air Flow	Range	Area
CFM	0-999900	0-999.9 ft <sup>2</sup>
CMM	0-999900	0-999.9 m <sup>2</sup>

آدرس: تهران، خیابان مطهری، خیابان میرزای شیرازی شمالی، پلاک ۱۰، طبقه ۳

تلفکس: 88105813

تلفن: 88482667 --- 88482667






CFM/CMM Thermo-Anemometer

**Model: DT-850**

**Accessories:**

9V battery and Anemo probe, Gift box with carrying case.

**Application:**



**CFM/CMM Thermo-Anemometer**

DT-850 CFM/CMM Thermo-Anemometer remote sensor is the most popular model for HVAC applications.

Display Air Flow (CFM/CMM), or Air Velocity plus Temperature & Max/Min/Avg value  
Easy to set Area dimensions (cm<sup>2</sup>) stored in the meter's internal memory for the next power on  
Resolution of 0.01m/sec  
20 points average for Air Flow  
Super large LCD Backlit Display  
3% velocity accuracy via low friction 2.83"D (72mm) ball bearing vane wheel on 3.9ft (120cm) cable  
Low battery indication and Auto Power Off

آدرس: تهران، خیابان مطهری، خیابان میرزای شیرازی شمالی، پلاک ۱۰، طبقه ۳

تلفکس: 88105813

تلفن: 88482667 --- 88482667