

CMM/CFM Thermo-Anemometers

Model: DT-8893/8894



Features:

Simultaneous display of Air Flow or Air Velocity plus Ambient Temperature
Easy to set Area dimensions (cm ²) are stored in the meter's internal memory for the next power on
Resolution of 0.01m/sec
20 points average for Air Flow
Super large (9999 counts) LCD Backlit Display
3% velocity accuracy via low friction 2.83"D (72mm) ball bearing vane wheel on 3.9ft (120cm) cable
Complete with vane sensor with 3.9ft (120cm) cable, 9V battery, and protective rubber holster
MAX/MIN, Data Hold functions

Specifications:

Air Velocity	Range	Accuracy	8893	8894
m/s(meter per second)	0.40~30.00	±3% ±0.20m/s	*	*
ft/min(feet per minute)	80~5900	±3% ±40ft/min	*	*
km/h(kilometers per hour)	1.4~108.0	±3% ±0.8km/h	*	*
MPH(miles per hour)	0.9~67.0	±3% ±0.4MPH	*	*
Knots(nautical miles per hour)	0.8~58.0	±3% ±0.4knots	*	*
Air Temperature	-10-60°C(14-140°F)	± 2.0°C(4.0°F)	*	*
InfraRed Temperature	-50 to -20°C(-58 to -4°F)	± 5.0°C(9.0°F)		*
	-20 to 500°C(-4 to 932°F)	±2% reading		*
Air Flow	Range	Area		
CFM	0-999900	0-999.9 ft ²	*	*
CMM	0-999900	0-999.9 m ²	*	*

آدرس: تهران، خیابان مطهری، خیابان میرزای شیرازی شمالی، کوچه نعیمی، پلاک ۱۰، طبقه ۳

تلفکس: 88105813

تلفن: 88482667 --- 88482667



CMM/CFM Thermo-Anemometers

Model: DT-8893/8894

Accessories:

9V battery, USB cable, software,
Anemo probe and Gift box with carrying case.

Application:



CMM/CFM Thermo-Anemometers

CFM/CMM Thermo-Anemometer with built-in non-contact IR Thermometer measure remote surface temperature to 500°C (932°F) and 30:1 distance to spot ratio.

