www.cem-meter.ir

Heavy Duty Industrial Digital Multimeter

Model: DT-9960/9961/9961W/9962/9962T/9963/9963T



www.cem-meter.ir

DT-9960, 9961, 9961W, 9962 and 9962T series are the new 4000 counts multimeters. 9963/9963T are 6000 counts multimeters. They are a combination of precision, easy-to -use, safety and reliability. 9962T /9963T have True RMS AC Voltage, Current readings, MAX-MIN recording, Peak recording, as well as Frequency and Capacitance readings. DT-9961W has wireless USB interface.

Safety Conformance

EN61010-1 CAT IV 600V, CAT III 1000V

1000V input protection on all ranges

10A/1000V & 0.5A/1000V fuses protection on current ranges

Features:

Features	DT-9960	DT-9961/9961W	DT-9962/9962T	DT-9963/9963T
Digital display counts	4000	4000	4000	6000
True RMS measurement		9961W	9962T	9963T
Safety design	*	*	*	*
Relative Zero	*	*		*
Data Hold	*	*	*	*
MAX/MIN recording mode			*	*
Auto Power Off	*	*	*	*
Peak Capture mode			*	
Wide capacitance range			40mF	1000uF
Analog barograph/segment			* /42	* /61
NCV Function	*	*	*	*

www.cem-meter.ir

Heavy Duty Industrial Digital Multimeter

Model: DT-9960/9961/9961W/9962/9962T/9963/9963T

Specifications:

Function	Max. Range	Accuracy	DT-9960	DT-9961/9961W	DT-9962/9962T	DT-9963/9963T
Voltage DC	1000V	±0.5%	*	*	*	*
Voltage AC	1000V	±0.8%	*	*	*	*
Current DC	10A	±1.2%	*	*	*	*
Current AC	10A	±1.8%	*	*	*	*
Resistance	40ΜΩ	±0.8%	*	*	*	*
Duty Cycle	99.90%	±1.2%	*	*	*	*
Frequency	10MHz	±1.5%	*	*	*	*
Capacitance	100μF / 40mF	±3.0%	100μF	100μF	40mF	1000μF
Temperature	760°C / 1400°F	±3.0%		*	*	*
Diode and Continuity			*	*	*	*

Accessories:

www.cem-meter.ir

Test leads, 9V battery, Type K temperature probe (9961/9961W/9962/9962T/9963/9963T) and gift box.

Application:





Heavy Duty Industrial Digital Multimeter

DT-9960, 9961, 9961W, 9962 and 9962T series are the new 4000 counts multimeters. 9963/9963T are 6000 counts multimeters. They are a combination of precision, easy-to -use, safety and reliability. 9962T /9963T have True RMS AC Voltage, Current readings, MAX-MIN recording, Peak recording, as well as Frequency and Capacitance readings. DT-9961W has wireless USB interface.

Safety Conformance EN61010-1 CAT IV 600V, CAT III 1000V

1000V input protection on all ranges

10A/1000V & 0.5A/1000V fuses protection on current ranges

آدرس: تهران،خیابان مطهری،خیابان میرزای شیرازی شمالی،کوچه نعیمی ،پلاک ۱۰،طبقه ۳