

## Refrigerant Leak Detector

Model: GD-3303



16" inch Gooseneck detector is easy to measure the hard-reached areas.

Highly sensitive and reliable

Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak.

Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate.

Pinpoint small Leaks: Detects all Refrigerant leaks even tiny leaks.

### Features:

16" inch Gooseneck detector is easy to measure the hard-reached areas.
Highly sensitive and reliable
Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak.
Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate.
Pinpoint small Leaks: Detects all Refrigerant leaks even tiny leaks.

### Specifications:

Pump driven field adjustable range	10ppm
Sensor Type	Solid State
Alarm	Visible & Audible at 10% LEL for Refrigerant Leaks. Can be calibrated for other concentrations or gases.
Warm-Up	Approx. 1 minute
Response Time	Less than 2 sec. (up to 40% LEL)
Duty Cycle	Intermittent
Probe Length	16"
Battery	3 "C" Alkaline


## Refrigerant Leak Detector

Model: GD-3303

### Accessories:

----

### Application:



**Refrigerant Leak Detector**

16" inch Gooseneck detector is easy to measure the hard-reached areas.

Highly sensitive and reliable

Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak.

Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate.

Pinpoint small Leaks: Detects all Refrigerant leaks even tiny leaks.