Moisture Meters

Model: DT-129/DT-129B



Features:

1.1	Larg	eΙ	CD	h (isr	าโลง	v
	Luis			· u	IJĸ	,ıu	v

2. Automatically Temperature Corrected (ATC) Readings when used with the temperature probe

3.Readings with Moisture Probe or Hammer Electrode

4.Readings with Integral electrode Pins

Specifications:

Measuring principle	Electrical resistance		
Electrode length	8mm		
Electrodes	Integrated, replaceable		
Measuring range	Wood:6-99.9%		
Display Accuracy	Wood: ±1%		
Battery	2×AAA		
Temperature measuring	0-60°C		
Ambient temperature	0-40°C		
Ambient moisture	0-85%		

Accessories:

Gift Box with Carrying Case

Moisture Meters

Model: DT-129/DT-129B

Applications:



Moisture Meters

DT-129 is a conductivity moisture instrument designed for use in wood, used to measure the moisture level in sawn timber (also cardboard, paper) and hardened materials (plaster, concrete and mortar). They display the moisture level. The instruments have an average adjustment for European wood based on a wood temperature of 20°C.

DT-129B is with various professional remote probe.

- •Large LCD display
- Automatically Temperature Corrected (ATC) Readings when used with the temperature probe
- •Readings with Moisture Probe or Hammer Electrode
- •Readings with Integral electrod Pins

آدرس: تهران،خیابان مطهری،خیابان میرزای شیرازی شمالی،پلاک ۱۰،طبقه ۳